



Owens Corning
PinkWrap® Housewrap,
the brand trusted to
protect your home
from moisture and the
elements.

PRODUCT DATA

PinkWRAP® Housewrap is a woven polyolefin fabric engineered to be a weather resistant barrier. PinkWRAP® Housewrap reduces the air infiltration through residential and commercial exterior side wall construction. PinkWRAP® Housewrap has microperforations that permit trapped moisture to escape from the wall to the exterior. PinkWRAP® Housewrap is translucent to allow installers to see the framing underneath. PinkWRAP® Housewrap has excellent tensile strength and tear resistance to withstand installation and wind driven loads. PinkWRAP® Housewrap can be left uncovered for up to 300 days before siding is installed. PinkWRAP® Housewrap meets the requirements of a weather resistant barrier as defined by ICC-ES Acceptance Criteria AC 38. See ICC Evaluation Services ESR 2801. PinkWRAP® Housewrap also meets the requirements for a Grade D building paper. Meets requirements for NFPA 101 Life Safety Code Class A material.

Weight	14.5 pounds/1,000 sq. feet
--------	----------------------------

Available Sizes	
Width & Length (ft)	Rolls per Pallet
3x100	150
4.5x100	100
9x100	50
10x100	
9x150	45
10x150	
9x195	40
10x195	
30 Pallets per truckload	

Property	Test Method	Actual	Required
Tensile Strength (lbs./in., MD/CD)	ASTM D 828	60 / 44	20 / 20
Trapezoidal Tear Strength (lbs., MD/CD)	ASTM D 1117	37 / 49	-
Water Resistance (10 min. minimum)	ASTM D 779	>60	10 minute Minimum
Water Vapor Transmission Rate (g/m ² /24 hrs)	ASTM E 96 - Procedure A Dry Cup (75 F, 50% RH)	52	> 35
Water Vapor Permeance Rate (perms)	ASTM E 96 - Procedure A Dry Cup (75 F, 50% RH)	7.7	> 5
Fire Characteristics – Flame Spread	ASTM E 84	5	< 25
Fire Characteristics – Smoke	ASTM E 84	30	< 450
Application Exposure (months)	Ambient exposure	9	N/A

BILD-R-TAPE®



BILD-R-TAPE® construction tape is a multi-purpose construction tape assembled using an acrylic based, pressure-sensitive adhesive combined with polypropylene film.

- Eliminate Drafts
- Easy to Install
- Meets the requirements of all applicable building codes in the US and Canadian markets.

WEATHERESIST®



WEATHERESIST® self-adhesive flashing tape, uniquely formulated to combine low temperature adhesion with high temperature stability and strength to provide an excellent product for sealing joints around window and door openings.

- Stops Window and Door Drafts
- No Messy Foam or Waste
- Easy Application & Saves Time and Money





*Good building practices include back priming of any porous siding before installation (such as wood, stucco, cement siding).

Per manufacturer's instructions, installation of housewrap under porous siding must have .40" (10mm) air space between housewrap and the porous material. PINKWRAP Housewrap provides a weather resistant barrier for the exterior building sheathing during construction. While PINKWRAP Housewrap can be left exposed for up to 300 days, Owens Corning recommends that PINKWRAP Housewrap be covered as soon as practical to ensure its optimal performance as an air and moisture barrier.

Building Code Compliance: See BOCA Research Report No. 99-50; See ICBO Evaluation Report No. 4649; see SBCCI Compliance Report No. 9769B. HUD/FHA UU-B-790A, Equivalent to Grade "D" paper.

Owens Corning believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Owens Corning does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting injury, damage or loss. NO WARRANTY, EXPRESSED OR IMPLIED, IS GIVEN AS TO THE MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR OTHERWISE WITH RESPECT TO THE PRODUCTS REFERRED TO.



INNOVATIONS FOR LIVING™

OWENS CORNING FOAM INSULATION, LLC

ONE OWENS CORNING PARKWAY

TOLEDO, OHIO, USA 43659

1-800-GET-PINK™

www.owenscorning.com

Pub. No. 10010510 Printed in U.S.A. February 2009. THE PINK PANTHER™ & © 1964–2009 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2009 Owens Corning.